## **Technical Manual**

# RS 9 Kappa



## Kappa Series 4-Way Speaker System

### **SPECIFICATIONS**

#### **ACOUSTIC & ELECTRICAL SPECIFICATIONS:**

• Nominal Impedance: 4 to 6 ohm

Power Rating: 60-340 watts RMS

• Efficiency: 102 dB SPL @1 watt, 1 meter

Crossover Frequencies: 80Hz, 800Hz, 4500Hz
Frequency Response: 29Hz-45kHz +/-3dB

#### **PRODUCTION HISTORY**

- Introduced in 1987
- Discontinued 1989
- Original Retail Price: \$1,499.00/each

#### SEE BACK FOR WIRING DIAGRAM

#### **PHYSICAL SPECIFICATIONS:**

- 1x SEMIT k Supertweeter
- 1x EMIT k Tweeter
- 1x 3" Edgewound Voice Coil Polydome k Midrange Driver
- 1x 5" Polypropylene/graphite Diaphram Polygraph k
- 2x 12" Cast Frame, L/C Tuned Woofers

• Dimensions: 59.5"H x 21.5"W" x 8"D

151.1cm(H) x 54.6cm(W) x 20.3cm(D)

Cabinet Not Sold
Base #659-3261
Grille #NLA
Crossover #015-3254-D
Binding Post #528-3238

## **TECHNICAL INFORMATION**



C-EMIT #902-2645B



TWEETER #902-3082N






MIDRANGE #902-3075



MID-BASS COUPLER #902-3068



12" WOOFER #902-3054

C3 3µF PP (SOLEN)

SCHEMATIC DIAGRAM

C1 2µF PP (SOLEN)